Exhibit Q: RF Exposure TEB-HUNTSU864

General Information

Applicant: Hunt Technologies, LLC FCC ID: TEB-HUNTSU864 Device Category: Mobile Environment: General Population/Uncontrolled Exposure

Technical Information 900 MHz

Antenna Type: PCB Inverted F ¼-Wave Monopole Antenna Gain: 5.15 dBi (Theoretical maximum) Transmitter Conducted Power: 27.48 dBm Maximum System EIRP: 32.63 dBm Operating Configuration: Fixed mounted Exposure Conditions: Greater than 20 centimeters

Technical Information 2400 MHz ZigBee

Antenna Type: PCB Inverted F ¼-Wave Monopole Antenna Gain: 5.15 dBi (Theoretical maximum) Transmitter Conducted Power: 21.20 dBm Maximum System EIRP: 26.35 dBm Operating Configuration: Fixed mounted Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm^2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE CALCULATIONS FOR MOBILE EQUIPMENT							
Transmit Frequency (MHz)	Conducted Power (dBm)	Conducted Power (mW)	Antenna Gain (dBi)	Antenna Gain (Linear)	Distance (cm)	Power Density (mW/cm ²)	Power Density Limit (mW/cm ²)
902.1	27.48	559.76	5.15	3.273	20	0.364	0.60
2405	21.20	131.83	5.15	3.273	20	0.0858	1.00

Installation Guidelines

"Exhibit D - Product Ship Sheet.pdf" contains the following text advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

Endpoint Location

To comply with FCC's RF exposure limits for general population/uncontrolled exposure, the antenna(e) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be collocated or operating in conjunction with any other antenna or transmitter.

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure, and the general population.