



CERTIFIED SOLAR COLLECTOR

SUPPLIER:
 Enerconcept Technologies
 56 Principale Ouest
 Magog, Quebec J1X2A5 Canada
 www.enerconcept.com

BRAND: Enerconcept
MODEL: Lubi
COLLECTOR TYPE: Air Transpired
CERTIFICATION #: 10001796
Original Certification: March 17, 2013
Expiration Date: March 11, 2023

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ANSI accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference.

COLLECTOR THERMAL EFFICIENCY and TEMPERATURE RISE (K at 913 W/m ²) (based on aperture area)									
Air Flow Rate	Wind Speed	0.0 m/s (0.0 mph)		1.0 m/s (2.2 mph)		1.4 m/s (3.1 mph)		3.0 m/s (6.7 mph)	
		η	Δ T	η	Δ T	η	Δ T	η	Δ T
1.2 scmm/m ² (4 scfm/ft ²)				0.67	22.4	0.67	22.5	0.65	21.8
2.1 scmm/m ² (7 scfm/ft ²)				0.73	14.2	0.73	14.3	0.73	14.3
3.1 scmm/m ² (10 scfm/ft ²)				0.68	9.6	0.72	10.1	0.73	10.3

TESTED COLLECTOR SPECIFICATIONS					
Gross Area:	4.494 m ²	48.37 ft ²	Dry Weight:	Not measured	
Net Aperture Area:	4.277 m ²	46.04 ft ²	Leakage Rate:	Not measured	
Absorber Area:	4.277 m ²	46.04 ft ²	Test Pressure:	Not conducted	

ADDITIONAL INFORMATION

SOLAR COLLECTOR CONSTRUCTION DETAILS OF THE TESTED COLLECTOR					
Gross Length:	2.448 m	Gross Width:	1.836 m	Gross Depth:	0.150 m

COLLECTOR MATERIALS					
Outer Cover:	Polymer Sheet	Enclosure back:	Wood	Back Insulation:	Foam
Inner Cover:	None	Enclosure side:	Steel	Side Insulation:	Foam
Absorber Description:	Steel Plate	Flow Pattern:	Plate		
Absorber Configuration:	Corrugated	Impact Safety Rating:	0		
Absorber Coating:	Black Paint	Absorptivity: 0.93	Emissivity: 0.88		

Test Lab:	Exova Canada, Inc.	Test Report Date:	March 11, 2011
Test Report Number:	08-08-0277-3 Rev1	Test conducted:	Indoors
Test Fluid:	Air	Tested in accordance with:	CSA F378-87
Back insulation during test	Foam	Back losses included in efficiency:	Yes

Remarks:

- Performance is unreliable if the collector is used at a pressure drop of less than 25 Pa because wind influences the performance unpredictably
- Wind impact on efficiency should not be extrapolated to large-scale systems because the ratio of wind-blown edge loss to gain across the surface area is diminished for large vs. small collectors (arrays).

DOSSIER: R-3837-2013 PHASE 3
 DEPOSEE EN AUDIENC
 Date: 21 MARS 2014
 Pièces n°: B-0413

Jean Higgins

Technical Director

www.solar-rating.org ♦ 400 High Point Drive, Suite 400 ♦ Cocoa, Florida 32926 ♦ (321) 213-6037 ♦ Fax (321) 821-0910

© Solar Rating & Certification Corporation™





CERTIFIED SOLAR COLLECTOR

SUPPLIER:
 Enerconcept Technologies
 56 Principale Ouest
 Magog, Quebec J1X2A5 Canada
 www.enerconcept.com

BRAND: Enerconcept
MODEL: UnitAir
COLLECTOR TYPE: Air Transpired
CERTIFICATION #: 10001797
Original Certification: March 17, 2013
Expiration Date: August 09, 2023

The solar collector listed below has been evaluated by the Solar Rating & Certification Corporation™ (SRCC™), an ANSI accredited and EPA recognized Certification Body, in accordance with SRCC OG-100, Operating Guidelines and Minimum Standards for Certifying Solar Collectors, and has been certified by the SRCC. This award of certification is subject to all terms and conditions of the Program Agreement and the documents incorporated therein by reference.

COLLECTOR THERMAL EFFICIENCY and TEMPERATURE RISE (K at 910 W/m ²) (based on aperture area)									
Air Flow Rate	Wind Speed	0.0 m/s (0.0 mph)		0.8 m/s (1.8 mph)		1.9 m/s (4.3 mph)		3.8 m/s (8.5 mph)	
		η	Δ T	η	Δ T	η	Δ T	η	Δ T
1.2 scmm/m ² (4 scfm/ft ²)				0.56	19.8	0.45	15.9	0.29	10.4
2.1 scmm/m ² (7 scfm/ft ²)				0.69	14.1	0.58	12.0	0.44	9.2
3.1 scmm/m ² (10 scfm/ft ²)				0.74	10.8	0.65	9.4	0.53	7.7

TESTED COLLECTOR SPECIFICATIONS					
Gross Area:	4.497 m ²	48.41 ft ²	Dry Weight:	Not measured	
Net Aperture Area:	4.497 m ²	48.41 ft ²	Leakage Rate:	Not measured	
Absorber Area:	4.497 m ²	48.41 ft ²	Test Pressure:	-0.44 kPa	

ADDITIONAL INFORMATION

SOLAR COLLECTOR CONSTRUCTION DETAILS OF THE TESTED COLLECTOR					
Gross Length:	2.444 m	Gross Width:	1.840 m	Gross Depth:	0.185 m

COLLECTOR MATERIALS					
Outer Cover:	None	Enclosure back:	Wood	Back Insulation:	Fiber
Inner Cover:	None	Enclosure side:	Steel	Side Insulation:	Fiber
Absorber Description:	Steel Plate	Flow Pattern:	Plate		
Absorber Configuration:	Corrugated, Perforated	Impact Safety Rating:	0		
Absorber Coating:	Black Paint	Absorptivity, Emissivity:	Not measured		

Test Lab:	Exova Canada, Inc.	Test Report Date:	August 09, 2011		
Test Report Number:	1 0-06-S0009RV1	Test conducted:	Indoors		
Test Fluid:	Air	Tested in accordance with:	CSA F378-87		
Back insulation during test	Foam	Back losses included in efficiency:	Yes		

Remarks:

- Performance is unreliable if the collector is used at a pressure drop of less than 25 Pa because wind influences the performance unpredictably
- Wind impact on efficiency should not be extrapolated to large-scale systems because the ratio of wind-blown edge loss to gain across the surface area is diminished for large vs. small collectors (arrays).
- All sizes of this collector are certified.

Jim Higgins

Technical Director

© Solar Rating & Certification Corporation™

www.solar-rating.org ♦ 400 High Point Drive, Suite 400 ♦ Cocoa, Florida 32926 ♦ (321) 213-6037 ♦ Fax (321) 821-0910

